

DIGITAL CHECK CHEXPRESS® CX35



The Secure Choice

The CX35 continues in the CX30 tradition while adding a sleek new dark design and great new features and functionality like automated cleaning, a smart button, and optional network connectivity

Affordable, Fast, Quality Scanning

The CX35 delivers fast quality scanning and features such as automated cleaning, optional network connectivity, and endorsement at an affordable price point. It includes all the features that made its predecessor the most popular RDC scanner in the world and adds multiple improvements we've developed in the meantime!

RNDIS Network Connectivity Option

The CheXpress CX35 introduces network functionality to specific models through the utilization of the Remote Network Driver Interface Specification (RNDIS) and Digital Check's SecureLink 2.0 API. Furthermore, it includes SimpleSwitch Connectivity enabling users the ability to switch between USB mode or a network connection with a few presses of the Smart Button.

Energy Efficient

The CX35 uses 600 dpi image sensors and Best Read® image enhancement technology to produce legible high-resolution images. The scanner combines MICR reading with OCR verification to increase overall read accuracy. So whether the check has a busy background or is written with gel pen ink, the CX35 will provide accurate read rates for your application.

KEY BENEFITS

- Easy Single-feed Scanning
- Optional Network-enabled via RNDIS
- Automated Cleaning Mode
- Quiet and Fast – Scan Up to 30 Documents Per Minute
- Engineered for Durability

TECHNICAL SPECIFICATIONS

Unit Size

Height: 7.47" (18.97 cm)

Width: 3.9" (9.96 cm)

Length: 9.38" (23.83 cm)

Weight: 3.72 lb. (1.8 kg)

Document Size

Document Height: 2.12"–4.25" (54 - 108 mm)

Image Capture Height: Up to 4.177" (106 mm)

Document Length: 3.19"–8.98" (81–228 mm)

Document Thickness

Scan & Return: 0.0032" - 0.0058" (0.081 - 0.147 mm)

Pass Through: 0.0032" - 0.0090" (0.081 - 0.229 mm)

Throughput

Scan and Return Mode: Up to 30 documents per minute

Connectivity

High-speed USB 2.0 cable and power supply included

Image Sensor

Resolution: 600 dpi

Light Source: Tri-Color LEDs

Supported Operating Systems

Windows 10® (32/64 bit)

Windows 11® (32/64 bit)

Mac OS X

Linux OS

Electrical

Power Consumption: 24 Watts

Input Voltage: 100 to 240 VAC, 50/60 Hz

Separate Standard Power Supply: Auto sensing for voltage

Environmental

Operating Temperature: 60°–90° F (15°–32° C)

Operating Humidity: 35–85% non-condensing

Productivity Functions (Smart Button)

Power on/off

Eject

Activate Automated Cleaning

Standard Warranty

1 Year